

Product Size Guide

Access Covers

Dimensions in mm		B125	B125	B125	C250	D400	D400	F900
L	W	Composite	Concrete	Recessed	Composite	Composite	Ductile	Ductile
300	300	■	■	■	■			
380	230		■	■			■	
420	240		■					
450	300	■	■	■	■			
450	450	■	■	■	■		■	
500	500	■	■	■	■			
530	380	■	■	■				
600	450	■	■	■	■			
600	600	■	■	■	■		■	■
675	675			■			■	■
725	255		■	■				
750	600	■	■	■	■			
750	675		■				■	
750	750	■	■	■	■		■	
800	800	■	■	■	■			
885	530	■			■			
900	450	■	■	■	■		■	
900	600	■	■	■	■		■	
900	675							
900	900	■	■	■	■		■	■
915	445	■	■	■				
915	915	■	■	■	■			
1000	600							
1000	1000	■	■		■			
1160	380	■	■		■			
1200	600	■	■	■	■			
1200	675						■	■
1200	900	■	■	■	■		■	
1200	1200	■	■	■	■		■	
1310	610	■	■	■	■		■	
1300	850		■	■			■	
1380	530	■						
1500	750	■	■	■	■		■	
1500	1500	■	■	■	■		■	
1800	675	■	■	■			■	■
1800	1800	■	■	■			■	
1900	1200	■			■			
1900	1500					■		
2000	600	■			■			
2000	2000	■	■	■				
2300	1500					■		
2300	1900					■		
2300	2300					■		
2700	1500					■		
2700	2300					■		
2500	1200	■			■			
2500	2500	■	■	■				
3000	3000	■	■	■				
3100	1500					■		
3100	1900					■		
3100	2300					■		
3100	2700					■		
3100	3100					■		
3900	1500					■		
3900	1900					■		
3900	2300					■		
3900	2700					■		
3900	3100					■		
4700	1500					■		
4700	1900					■		
4700	2300					■		
4700	2700					■		
4700	3100					■		
5500	1500					■		
5500	1900					■		
5500	2300					■		
5500	2700					■		
5500	3100					■		
6300	1500					■		
6300	1900					■		
6300	2300					■		
6300	2700					■		
6300	3100					■		

Composite (B125-C250 -D400)

Composite covers offer a lightweight cover with no reduction in loading performance. A wide range of sizes can be manufactured utilising multi-cover frames and there are options for bespoke customer badging. Covers can also be fitted with locking features to enhance the security of the assets below.

Concrete (B125)

Concrete Infill covers offer flexibility in size and design. A wide range of sizes can be manufactured utilising multi-cover frames and there are options for bespoke customer badging. Covers can also be fitted with locking features to enhance the security of the assets below.

Recessed (B125)

The Recessed cover range has developed a reputation in the construction industry for being high-quality, safe to use, value for money and secure when installed. Recessed covers are the sole approved footway cover used by end users such as BT Openreach and Virgin Media.

Ductile (D400)

D400 ductile iron access covers fully comply with BS EN 124:1994 and carry the British Standard kitemark.

Ductile (F900)

The range of F900 ductile iron access covers fully comply with BS EN 124:1994 and carry the British Standard kitemark.