



# Product Size Guide:

## AX-S™ Covers

Dimensions in mm		B125	B125	B125	C250	D400	F900
		Composite	Concrete	Recessed	Composite	Ductile	Ductile
L	W						
300	300	■	■	■	■		
380	230		■	■		■	
420	240		■				
450	300	■	■	■	■		
450	450	■	■	■	■	■	
500	500	■	■	■	■		
530	380	■	■	■			
600	450	■	■	■	■		
600	600	■	■	■	■	■	■
675	675			■		■	■
725	255		■	■			
750	600	■	■	■	■		
750	675		■			■	
750	750	■	■	■	■	■	
800	800	■	■	■	■		
885	530	■			■		
900	450	■	■	■	■	■	
900	600	■	■	■	■	■	
900	675						
900	900	■	■	■	■	■	■
915	445	■	■	■			
915	915	■	■	■	■		
1000	600						
1000	1000	■	■		■		
1160	380	■	■		■		
1200	600	■	■	■	■		
1200	675					■	■
1200	900	■	■	■	■	■	
1200	1200	■	■	■	■	■	
1310	610	■	■	■	■	■	
1300	850		■	■		■	
1380	530	■					
1500	750	■	■	■	■	■	
1500	1500	■	■	■	■	■	
1800	675		■	■		■	■
1800	1800	■	■	■		■	
1900	1200	■			■		
2000	600	■			■		
2000	2000	■	■	■			
2500	1200	■			■		
2500	2500	■	■	■			
3000	3000	■	■	■			

\*Bespoke options are available. Please contact for further details.

**Composite (B125 - C250)**

AX-S™ Composite covers offer a lightweight cover with no reduction in loading performance. A wide range of sizes can be manufactured utilising multi-cover frames and there are options for bespoke customer badging. Covers can also be fitted with locking features to enhance the security of the assets below.

**Concrete (B125)**

AX-S™ Concrete Infill covers offer flexibility in size and design. A wide range of sizes can be manufactured utilising multi-cover frames and there are options for bespoke customer badging. Covers can also be fitted with locking features to enhance the security of the assets below.

**Recessed (B125)**

The AX-S™ Recessed cover range has developed a reputation in the construction industry for being high-quality, safe to use, value for money and secure when installed. AX-S™ Recessed covers are the sole approved footway cover used by end users such as BT Openreach and Virgin Media.

**Ductile (F900)**

The range of F900 ductile iron access covers fully comply with BS EN 124:1994 and carry the British Standard kitemark.

**Ductile (D400)**

D400 ductile iron access covers fully comply with BS EN 124:1994 and carry the British Standard kitemark.